

Beat-Sonic®

ACURA RL

HSA-13

User's Manual

NO:000001

Thank you for purchasing Beat-Sonic USA Electronic Adapter, HSA-11.
Please read carefully and follow these instructions before installing this product.

Car Model	Year	Chassis Code
ACURA RL	1996~1998	KA9

Feartures:

For 1996-1998 Acura 3.5RL with factory navigation

Caution:

- Both left and right rear door SP. will be disabled after installation.
- A separate amplifier will need to be installed to power up these speakers.
- The Rearspeaker becomes either of a rear door or reartray speaker.
- Cannot use CD changer and optional DVD changer

Included in this kit:

Wiring Connector, Faceplate(1), Brackets(L,R), Nut(4),

⚠ Precautions BEFORE Installation Process

- Always disconnect the negative(-) terminal of the vehicle battery and drain all capacitors before installation.
- Use the masking tape to label the wires passing near the metal part of the car
- After the installation, make sure the brake lamps, headlights, turn signals and wipers work properly.

⚠ Caution Before starting installation, verify that the original audio system in the vehicle is fully functional. This kit will not remedy any issues that existed before the installation or faults in the original systems in the vehicle.

1 Removal of the Factory OEM Audio Head Unit

- 1.Remove the shift panel. (Hook×6)
- 2.Remove the air conditioner louver. (Hook×8)
- 3.Remove the audio ASSY. (Nut×4)

3 Installation of the New Head Unit

1. The brakets are installed in the new head unit.
- The panel are installed in the new head unit.

2 Installation of adaptor